



● Specifications

Type	Rated current AC-3(A)	Controlled power (kv)				
		220V	380V	415V	440V	660V
S-LC2-D0901	9	2.2	4	4	4	5.5
S-LC2-D1201	12	5.5	5.5	5.5	5.5	7.5
S-LC2-D1801	18	7.5	7.5	9	9	10
S-LC2-D2501	25	5.5	11	11	11	15
S-LC2-D3201	32	7.5	15	15	15	18.5
S-LC2-D4011	40	18.5	18.5	22	22	30
S-LC2-D5011	50	15	22	25	30	33
S-LC2-D6511	63	18.5	30	37	37	37
S-LC2-D8011	80	22	37	45	45	45
S-LC2-D9511	95	22	45	45	45	41

Size: S-LC2-D	115	1154	185	1854	265	2654	400	4004	500	630	780	
Maximum rated voltage	1000V	1000V	1000V	1000V	1000V	1000V	1000V	1000V	1000V	1000V	1000V	
Maximum thermal current 1 th	200A	200A	270A	270A	350A	350A	500A	500A	700A	1000A	1600A	
Maximum rated current LL: Long life/NL: 3ph 440V 50/60Hz	NL 120A	LL 115A NL 150A	NL 185A LL 185A NL 205A	NL 265A LL 265A NL 300A	NL 400A LL 400A NL 450A	NL 500A LL 630A NL 630A	NL 1000A LL 800A NL 780A					
Maximum standard power rating under duty Ac3	220V kw hp	30 40	30 40 45 60	55 75 55 75 63 85	75 100 75 100 90 125	110 150 110 150 132 180	132 180 132 180 160 220	200 270 200 270 220 300	220 250 220 250 250 335	250 335 250 335 335 400	335 400 335 400 400 500	400 500 400 500 500 680
	380V kw hp	55 75	55 75 75 100	90 125 90 125 110 150	132 180 132 180 160 220	200 270 200 270 220 300	220 300 220 300 250 340	250 335 250 335 335 400	335 400 335 400 450 540	335 400 335 400 450 540	400 500 400 500 540 680	500 680 500 680 680 800
	415/440V kw hp	60 80	60 80 80 110	100 135 100 135 110 150	140 190 140 190 160 220	220 300 220 300 250 340	220 300 220 300 280 380	280 355 280 355 355 450	355 450 355 450 450 570	355 450 355 450 450 570	450 570 450 570 570 720	570 720 570 720 720 800